



NPN DUAL SMALL SIGNAL SURFACE MOUNT TRANSISTOR

- **Epitaxial Die Construction**
- Complementary PNP Type Available (BC857BV)
- Ultra-Small Surface Mount Package
- Lead Free By Design/RoHS Compliant (Note 3)
- "Green" Device (Note 5 and 6)

Mechanical Data

- Case: SOT-563
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminal Connections: See Diagram
- Terminals: Finish Matte Tin annealed over Alloy 42 leadframe. Solderable per MIL-STD-202, Method 208
- Marking Information: K4V, See Page 2
- Ordering & Date Code Information: See Page 2
- Weight: 0.003 grams (approximate)







See Note 1

SOT-563									
Dim	Min	Max	Тур						
Α	0.15	0.30	0.25						
В	1.10	1.25	1.20						
С	1.55	1.70	1.60						
D	_	-	0.50						
G	0.90	1.10	1.00						
Н	1.50	1.60							
K	0.56	0.60	0.60						
L	0.10	0.30	0.20						
M	0.10	0.18	0.11						
All Dimensions in mm									

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Value	Unit		
Collector-Base Voltage		V_{CBO}	50	V		
Collector-Emitter Voltage		V _{CEO}	45	V		
Emitter-Base Voltage		V _{EBO}	6.0	V		
Collector Current		lc	100	mA		
Power Dissipation	(Note 2)	P_d	150	mW		
Thermal Resistance, Junction to Ambient	(Note 2)	$R_{\theta JA}$	833	°C/W		
Operating and Storage Temperature Range		T _j , T _{STG}	-55 to +150	°C		


Electrical Characteristics @TA = 25°C unless otherwise specified


Characteristic	Symbol	Min	Тур	Max	Unit	Test Condition	
Collector-Base Breakdown Voltage	(Note 4)	V _{(BR)CBO}	50		_	V	$I_C = 10 \mu A, I_B = 0$
Collector-Emitter Breakdown Voltage	(Note 4)	V _{(BR)CEO}	45	_	_	V	$I_C = 10 \text{mA}, I_B = 0$
Emitter-Base Breakdown Voltage	(Note 4)	V _{(BR)EBO}	6	_	_	V	$I_E = 1\mu A, I_C = 0$
DC Current Gain	(Note 4)	h _{FE}	200	290	450	_	$V_{CE} = 5.0V, I_{C} = 2.0mA$
Collector-Emitter Saturation Voltage	(Note 4)	V _{CE(SAT)}	_	_	100 300	mV	I_C = 10mA, I_B = 0.5mA I_C = 100mA, I_B = 5.0mA
Base-Emitter Saturation Voltage	(Note 4)	V _{BE(SAT)}	_	700 900	_	mV	I_C = 10mA, I_B = 0.5mA I_C = 100mA, I_B = 5.0mA
Base-Emitter Voltage	(Note 4)	V_{BE}	580 —	660 —	700 770	mV	V_{CE} = 5.0V, I_{C} = 2.0mA V_{CE} = 5.0V, I_{C} = 10mA
Collector-Emitter Cutoff Current	(Note 4)	I _{CBO}	1	_	15 5.0	nΑ μΑ	V _{CB} = 30V V _{CB} = 30V, T _A = 150°C
Gain Bandwidth Product		f _T	100	_	_	MHz	$V_{CE} = 5.0V, I_{C} = 10mA,$ f = 100MHz
Output Capacitance		C _{OBO}	_	_	4.5	pF	V _{CB} = 10V, f = 1.0MHz
Noise Figure		NF	_	_	10	dB	V_{CE} = 5V, R _S = 2.0kΩ, f = 1.0kHz, BW = 200Hz


Notes:

- 1. Package is non-polarized. Parts may be on reel in orientation illustrated, 180° rotated, or mixed (both ways).
- 2. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch; pad layout as shown on Diodes Inc. suggested pad layout document AP02001, can be found on our website at http://www.diodes.com/datasheets/ap02001.pdf.
- 3. No purposefully added lead.
- Short duration pulse test used to minimize self-heating effect.
- Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
- Product manufactured with Date Code UO (week 40, 2007) and newer are built with Green Molding Compound. Product manufactured prior to Date Code UO are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.









1,000 V_{CE} = 5V V_{CE}




Ordering Information (Note 7)

Device	Packaging	Shipping
BC847BV-7	SOT-563	3000/Tape & Reel

Notes: 7. For packaging details, go to our website at http://www.diodes.com/datasheets/ap02007.pdf.

Marking Information



K4V = Product Type Marking Code YM = Date Code Marking Y = Year (ex: T = 2006) M = Month (ex: 9 = September)

Date Code Key

Date Code Ney												
Year	2003	2004	20	05	2006	2007	2008	2009	20	10	2011	2012
Code	Р	R		3	T	U	V	W		X	Y	Z
Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	0	N	D



IMPORTANT NOTICE

- 1. DIODES INCORPORATED AND ITS SUBSIDIARIES ("DIODES") MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).
- 2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes products. Diodes products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of the Diodes products for their intended applications, (c) ensuring their applications, which incorporate Diodes products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.
- 3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.
- 4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.
- 5. Diodes products are provided subject to Diodes' Standard Terms and Conditions of Sale (https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.
- 6. Diodes products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.
- 7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.
- 8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

Copyright © 2021 Diodes Incorporated

www.diodes.com