



ONE CHANNEL HIGH SURGE TVS DIODE

Product Summary

V _{BR (MIN)}	PPP (MAX)	I _{R (MAX)}
30.9V	4000W	200nA

Description

The D28V0S1U3LP20 is new generation TVS and is a design which includes a uni-directional surge rated clamping cell to protect one power line or control line in an electronic system. The robust diode can safely absorb repetitive ESD strikes at ±30kV (contact and air discharge, IEC 61000-4-2) without performance degradation.

Applications


- USB VBUS protections
- Panel modules
- Touch Panels
- Notebooks and handhelds

Features

- Provides ESD Protection per IEC 61000-4-2 Standard:
 Air ±30kV, Contact ±30kV
- One Channel of ESD Protection
- Low Channel Input Capacitance
- Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)
- Halogen and Antimony Free. "Green" Device (Note 3)
- For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please <u>contact us</u> or your local Diodes representative. <u>https://www.diodes.com/quality/product-definitions/</u>

Mechanical Data

- Package: U-DFN2020-3
- Package Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: NiPdAu over Copper Leadframe. Solderable per MIL-STD-202, Method 208 @
- Weight: 0.004 grams (Approximate)



U-DFN2020-3 (Type C)



1 and 2 must be electrically connected at the PCB

Ordering Information (Note 4)

Notes:

Part Number	Paakaga	Marking Code	Reel Size	Tape Width	Pa	cking
Fart Number	Package	Marking Code	(inches)	(mm)	Qty.	Carrier
D28V0S1U3LP20-7	U-DFN2020-3 (Type C)	8N	7	8	3,000	Tape & Reel

1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.

2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.

3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

4 For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.



Marking Information



8N = Product Type Marking Code YM = Date Code Marking Y = Year (ex: L = 2024) M = Month (ex: 9 = September)

Date Code Key

2410 0040 110)												
Year	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035
Code	L	М	Ν	Р	R	S	Т	U	V	W	Х	Y
Month	Jan	Feb	Mar	Apr	Мау	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	0	N	D

Maximum Ratings (@TA = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit	Conditions
Peak Pulse Power Dissipation	P _{PP}	4000	W	8/20µs (Note 6)
Peak Pulse Power Dissipation	Ppp	260	W	10/1000µs
ESD Protection – Contact Discharge	Vesd_contact	±30	kV	Standard IEC 61000-4-2
ESD Protection – Air Discharge	Vesd_air	±30	kV	Standard IEC 61000-4-2

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 5)	PD	500	mW
Thermal Resistance, Junction to Ambient $T_A = +25^{\circ}C$	Reja	250	°C/W
Operating and Storage Temperature Range	TJ, TSTG	-55 to +150	٥C


Electrical Characteristics (@TA = +25°C, unless otherwise specified.)

Part Number	Reverse Standoff Voltage V _{RWM} (V)		down V VBR (V) IR = 1mA	Ū	Reverse Leakage Current Iгм (nA) at Vrwм	Rated Peak Pulse Current I _{PPM} (A) 8/20µs	Rated Peak Pulse Current I _{PPM} (A) 10/1000µs	Clamping Voltage V _{CL} (V) at IPPM 8/20µs	Clamping Voltage V _{CL} (V) at IPPM (A) 10/1000µs	Capacitance C⊤ (pF) V _R = 0V f = 1MHz
	Мах	Min	Тур	Max	Max	Max	Max	Max	Max	Тур
D28V0S1U3LP20-7	28	30.9	_	34.6	200	70	5.4	57.1	48.1	598

5. Device mounted on FR-4 PCB pad layout (2oz copper) as shown on Diodes Incorporated's suggested pad layout, which can be found on our website at Notes: http://www.diodes.com/package-outlines.html.
Clamping voltage value is based on an 8x20µs peak pulse current (I_{PP}) waveform, measured from Pin1 and Pin2 to Pin3.




D28V0S1U3LP20






Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.






U-DFN2020-3										
	(Type C)									
Dim	Min	Max	Тур							
Α	0.55	0.65	0.60							
A1	0.00	0.05	0.02							
A3			0.152							
b	0.25	0.35	0.30							
D	1.95	2.05	2.00							
D2	0.90	1.10	1.00							
E	1.95	2.05	2.00							
E2	1.40	1.60	1.50							
е		0.65BS	SC							
k			0.35							
L	0.35	0.45	0.40							
L1	0.20	0.30	0.25							
z			0.20							
All D	imens	ions ir	n mm							

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.



U-DFN2020-3	(Type C)

Dimensions	Value (in mm)
С	0.650
Х	0.600
X1	1.100
X2	0.350
X3	2.300
Y	0.400
Y1	1.600
Y2	1.700



IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.

3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.

4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.

Diodes' products provided subject Diodes' Standard and Conditions of are to Terms Sale (https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.

7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.

8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

9. This Notice may be periodically updated with the most recent version available at https://www.diodes.com/about/company/terms-and-conditions/important-notice

The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries. All other trademarks are the property of their respective owners. © 2024 Diodes Incorporated. All Rights Reserved.

www.diodes.com